

ZON™

BEARINGS FOR YOUR FUTURE



Sondermasse / Special Dimension Bearings





BEARINGS FOR YOUR FUTURE

Zen Ball Bearings are manufactured to the highest quality for standard and non-standard applications. Our technical department can modify any non-standard bearings to your specific requirements, regardless of quantity.

Apart from our extensive miniature ball bearing range of more than 1000 different types, ranging from 1-10 mm bore (Including inch dimensions), our range also includes Thin section, Three part thrust, Popular metric and any kind of non standard bearing. We are able to design bearings according to your requirements using new materials like ceramic or special steels for applications in Industry, Medicine, Chemistry and Food Processing.

Our technical department can modify any non-standard bearings to your specific requirements, even for small quantities.

For any items not listed in our catalogue, please contact our experienced sales team.



Zen Ball Bearings Shanghai has been awarded the German ISO TUV Rheinland certification for inspection of ZEN products.

This certification is the highest standard a business in our industry can achieve.

It is internationally recognised as a guarantee of quality, customer focus and continual improvement.



NUTR Stützrollen **NUTR Track Roller**



Wetterbeständig
Outdoor durability



Ölschmierung
Oil lubrication



Fettschmierung
Grease lubrication





Gummidichtscheiben verfügbar
Rubber seal option available



Metalldeckscheiben verfügbar
Metal shield option available

Sondermasse / Special Dimension Bearings



3

	Dimension (mm)			Dimension (inch)	Designation/Type		* Load Rating		* Limiting Speed x1000 rpm	Weight (g) approx.
	d	D	B	d	Chrome Steel		C, dyn. N	C, stat. N	Grease	
					2Z	2RS/2TS				
standard or flanged										
standard	6.000	21.00	6.00	-	626/21-2Z	-	2336	896	32.0	8 g
standard	8.000	22.00	6.00	-	608-2ZW6	-	3293	1379	34.0	12 g
standard	8.000	24.00	7.00	-	608/24-2Z	-	3293	1379	34.0	14 g
standard	8.000	26.00	7.00	-	608/26-2Z	-	3293	1379	34.0	15 g
standard	10.000	35.00	11.00	-	6200/35-2Z	-	5100	2390	24.0	45 g
standard	12.700	32.00	10.00	0.500 (1/2)	6201-2Z1/2	6201-2RS1/2*	6800	3050	22.0	37 g
standard	13.000	32.00	10.00	-	6201-2Z/13	-	6800	3050	22.0	37 g
standard	15.875	35.00	11.00	0.625 (5/8)	6202-2Z5/8	6202-2RS5/8*	7650	3750	20.0	45 g
standard	16.000	35.00	11.00	-	6202-2Z/16	-	7650	3750	20.0	45 g
standard	15.000	47.00	11.00	-	6202/47-2Z	6202/47-2RS*	7650	3750	20.0	100 g
standard	15.875	40.00	12.00	0.625 (5/8)	6203-2Z5/8	6203-2RS5/8*	9550	4800	17.0	67 g
standard	16.000	40.00	12.00	-	6203-2Z/16	-	9550	4800	17.0	67 g
standard	19.050	40.00	12.00	-	6203-2Z3/4	6203-2RS3/4*	9550	4800	17.0	67 g
standard	19.050	47.00	12.00	0.750 (3/4)	6204-2Z3/4	-	12800	6600	15.0	107 g
standard	22.225	47.00	14.00	0.750 (3/4)	6204-2Z7/8	-	12800	6600	15.0	107 g

www.zen.biz

Alle Rechte vorbehalten, kein Teil des Katalogs darf in irgendeiner Form (Druck, Fotokopie, Mikrofilm oder in einem anderen Verfahren) ohne Genehmigung reproduziert oder unter Verwendung elektronischer Systeme verarbeitet, vervielfältigt oder verbreitet werden.

Copyright reserved. No part of the catalogue is to be copied, extracted or modified without explicit permission from the copyright holder.

v.10 / 12



Bearings for your future